



ROUTING				
EXTERNAL CONNECTOR MINK-FCR 12#22, square 31.75		MCBH8FP with MCDLS-F (red Sleeve)		
PIN	Signal	PIN	Signal	Wire Color
1	Ext sensor 1 Out (+V1)	2	Pwr (+)	White
2	Ext sensor 1 Out GND (0/+V1 V) (*)	1	GND	Black
3	Ext sensor 2 Out (+V2)			
4	Ext sensor 2 Out GND (0/+V2 V) (*)			
5	Port X: RS422 TX(+)/RS232 TX(+)	5	RS 232 Rx	Orange
6	Port X: RS422 TX(-)			
7	Port X: RS422 RX(-)/RS232 RX(+)	3	RS 232 Tx	Black
8	Port X: RS422 RX(+)			
9	Ext Pulse OUT +	7	Sync Line	Black/White
10	Ext Pulse OUT -	1	GND	Black
11	Port : GND (**)	1	GND	Black
12	Pulse C : IN TTL			

No. ARTICLE	REFERENCE TECHNIQUE	DESIGNATION
1	MINK-12#22-CCP-Ti	OVER-MOULED 12PTS SEACON CONNECTOR
2	MCIL8F_SUBC with MCDLS-F and Snap Ring (red Sleeve)	8 PTS SUBCONN CONNECTOR FEMALE

00	Ajout d'une annotation sur le placement de l'étiquette	TMA	14/06/2019	En cours
INDICE	DESCRIPTION DE LA REVISION	CREATION	ETAT	
MATIERE:	Matériau <non spécifié>	√Ra ---	Tol. Gén.: ---	MASSE: 157.97
TRAITEMENT:	---	FINITION:	---	
Désignation <h2 style="text-align: center;">CABLE ROVINS DVL NORTEK</h2>				
		Classification	Référence de l'article	Référence du plan
Tél.: +33 1 30 08 98 88		SCA	SCA00570-E	PLA13921-AF
Ce document est la propriété de IXBLUE et ne peut être reproduit ou transmis sans son autorisation écrite. This document is the property of IXBLUE and shall not be reproduced nor transmitted without written approval.				Echelle 3:4 A3 1/1